

2019 SUPER DUTY F-SERIES TRUCKS

Order Guide Supplemental Reference

8/6/18

This supplement contains Maximum Payload Charts, Snow Plow Application Charts, Cab-to-Axle dimensions and Spring Selection Charts.

This information will help you in selecting the right truck to meet your customers' needs.

Please refer to the appropriate 2019 eSourceBook section for more complete weight rating information.

CONTENTS

Payload Package Selection Charts

F-250 SRW Pickup	1
F-350 SRW Pickup	2
F-350 DRW Pickup	3
F-450 DRW Pickup	4
F-350 SRW Chassis Cab	5
F-350 DRW Chassis Cab	6
F-450 Chassis Cab	7
F-550 Chassis Cab	8

Snow Plow Applications Charts	9
-------------------------------	---

Cab-to-Axle Dimension Chart	10
-----------------------------	----

Front Spring/GAWR Selection Charts

F-250 SRW Pickup	11
F-350 SRW Pickup/Pickup Box Delete	12
F-350 DRW Pickup/Pickup Box Delete	13
F-450 DRW Pickup	14
F-350 SRW Chassis Cab	15
F-350 DRW Chassis Cab	16
F-450 Chassis Cab	17
F-550 Chassis Cab	18

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts

8/6/2018

F-250 Pickup
Standard GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,000	4,270	10,000	3,990	10,000	3,880	10,000	3,890	10,000	3,660
	6.7L	10,000	3,450	10,000	3,180	10,000	3,050	10,000	3,060	10,000	2,830
4x4	6.2L	10,000	3,840	10,000	3,570	10,000	3,480	10,000	3,480	10,000	3,230
	6.7L	10,000	3,040	10,000	2,780	10,000	2,660	10,000	2,670	10,000	2,390

F-250 Pickup
Optional GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	9,900	4,170	9,900	3,890	9,900	3,780	9,900	3,790	9,900	3,560
	6.7L	9,900	3,350	9,900	3,080	9,900	2,950	9,900	2,960	9,900	2,730
4x4	6.2L	9,900	3,740	9,900	3,470	9,900	3,380	9,900	3,380	9,900	3,130
	6.7L	9,900	2,940	9,900	2,680	9,900	2,560	9,900	2,570	9,900	2,290

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts
8/6/2018

F-350 SRW Pickup
Standard Variable GVWR for 17" Wheel & Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,000	4,080	10,000	3,820	10,300	4,010	10,100	3,760	10,500	3,930
	6.7L	10,600	3,940	10,800	3,910	11,000	3,980	10,900	3,820	11,100	3,780
4x4	6.2L	10,300	3,960	10,400	3,800	10,700	3,990	10,500	3,750	10,800	3,810
	6.7L	11,000	3,920	11,100	3,790	11,300	3,860	11,200	3,710	11,500	3,760

F-350 SRW Pickup
Standard Variable GVWR for 18" Wheel & Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,400	4,420	10,500	4,260	10,800	4,450	10,600	4,200	10,900	4,280
	6.7L	11,100	4,380	11,200	4,250	11,500	4,420	11,300	4,170	11,500	4,130
4x4	6.2L	10,800	4,400	10,800	4,140	11,200	4,430	10,900	4,090	11,300	4,250
	6.7L	11,500	4,360	11,500	4,130	11,500	4,000	11,500	3,950	11,500	3,700

F-350 SRW Pickup
Standard Variable GVWR for 18"/20" All-Terrain & 20" All-Season Tire 4x4

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x4	6.2L	11,300	4,890	11,300	4,640	11,500	4,730	11,300	4,480	11,500	4,450
	6.7L	11,500	4,360	11,500	4,130	11,500	4,000	11,500	3,950	11,500	3,690

F-350 SRW Pickup
Optional Fixed 10,000-lb. GVWR

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	10,000	4,080	10,000	3,820	10,000	3,710	10,000	3,660	10,000	3,430
	6.7L	10,000	3,340	10,000	3,110	10,000	2,980	10,000	2,920	10,000	2,680
4x4	6.2L	10,000	3,660	10,000	3,400	10,000	3,290	10,000	3,250	10,000	3,010
	6.7L	10,000	2,920	10,000	2,690	10,000	2,560	10,000	2,510	10,000	2,260

F-350 SRW Pickup
Optional Fixed 9900-lb. GVWR (Available in Canada only)

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	9,900	3,980	9,900	3,720	9,900	3,610	9,900	3,560	9,900	3,330
	6.7L	9,900	3,240	9,900	3,010	9,900	2,880	9,900	2,820	9,900	2,580
4x4	6.2L	9,900	3,560	9,900	3,300	9,900	3,190	9,900	3,150	9,900	2,910
	6.7L	9,900	2,820	9,900	2,590	9,900	2,460	9,900	2,410	9,900	2,160

F-350 SRW Pickup
Optional GVWR Downgrade 17" Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x4	6.7L	---	---	---	---	---	---	---	---	11,400	3,660

F-350 SRW Pickup
Optional GVWR Downgrade 18" All-Season Tire

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.7L	---	---	---	---	11,400	4,320	---	---	11,400	4,030
4x4	6.7L	11,400	4,260	11,400	4,030	11,400	3,900	11,400	3,850	11,400	3,600

F-350 SRW Pickup
Optional Variable GVWR for 18"/20" All-Terrain & 20" All-Season Tire 4x4

Cab		Regular Cab		SuperCab				Crew Cab			
Wheelbase (in.)		141.6		148.0		164.2		159.8		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x4	6.2L	---	---	---	---	11,400	4,630	---	---	11,400	4,350
	6.7L	11,400	4,260	11,400	4,030	11,400	3,900	11,400	3,850	11,400	3,590

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts

8/6/2018

F-350 DRW Pickup
Maximum GVWR

Cab Wheelbase (in.)		Regular Cab 141.6		SuperCab 164.2		Crew Cab 176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	14,000	7,640	14,000	7,200	14,000	6,970
	6.7L	14,000	6,900	14,000	6,480	14,000	6,240
4x4	6.2L	14,000	7,230	14,000	6,780	14,000	6,550
	6.7L	14,000	6,510	14,000	6,060	14,000	5,790

F-350 DRW Pickup Box Delete
Maximum GVWR

Cab Wheelbase (in.)		Regular Cab 141.6		SuperCab 164.2		Crew Cab 176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.7L	13,000	6,320	13,000	5,900	13,000	5,660
4x4	6.7L	13,000	5,930	13,000	5,480	13,000	5,210

F-350 DRW Pickup
Optional GVWR Downgrade

Cab Wheelbase (in.)		Regular Cab 141.6		SuperCab 164.2		Crew Cab 176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.2L	13,000	6,640	13,000	6,200	13,000	5,970
	6.7L	13,000	5,900	13,000	5,480	13,000	5,240
4x4	6.2L	13,000	6,230	13,000	5,780	13,000	5,550
	6.7L	13,000	5,510	13,000	5,060	13,000	4,790

Note: 13,000 GVWR only available on 6.7L Diesel with Pickup Box Delete

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts
 8/6/2018

F-450 DRW Pickup
Standard GVWR

Cab		Regular Cab		Crew Cab	
Wheelbase (in.)		141.6		176.0	
Drive	Engine	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.7L	14,000	6,190	14,000	5,630
4x4	6.7L	14,000	5,880	14,000	5,310

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts

8/6/2018

F-350 SRW Chassis Cab
Optional Fixed 9800-lb. GVWR

		Regular Cab 60" CA		SuperCab 60" CA		Crew Cab 60" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
Drive	Engine						
4x2	6.2L	9,800	4,370	9,800	4,070	9,800	3,830
	6.7L	9,800	3,630	9,800	3,280	9,800	3,040
4x4	6.2L	9,800	3,960	9,800	3,640	9,800	3,420
	6.7L	9,800	3,190	9,800	2,850	9,800	2,620

F-350 SRW Chassis Cab
Optional Fixed 10,000-lb. GVWR

		Regular Cab 60" CA		SuperCab 60" CA		Crew Cab 60" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
Drive	Engine						
4x2	6.2L	10,000	4,520	10,000	4,220	10,000	3,980
	6.7L	10,000	3,780	10,000	3,430	10,000	3,190
4x4	6.2L	10,000	4,110	10,000	3,790	10,000	3,560
	6.7L	10,000	3,340	10,000	2,990	10,000	2,770

F-350 SRW Chassis Cab
Standard/Variable GVWR for 18" Wheels/Tires

		Regular Cab 60" CA		SuperCab 60" CA		Crew Cab 60" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
Drive	Engine						
4x2	6.2L	10,500	4,870	10,900	4,970	11,000	4,830
	6.7L	11,100	4,730	11,500	4,780	11,500	4,540
4x4	6.2L	10,900	4,860	11,300	4,940	11,400	4,820
	6.7L	11,500	4,690	11,500	4,350	11,500	4,120

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts

8/6/2018

F-350 DRW Chassis Cab
Standard Fixed GVWR

		Regular Cab				SuperCab		Crew Cab	
		60" CA		84" CA		60" CA		60" CA	
		Max		Max		Max		Max	
Drive	Engine	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)
4x2	6.2L	14,000	7,940	14,000	7,330	14,000	7,600	14,000	7,460
	6.7L	14,000	7,200	14,000	7,130	14,000	6,280	14,000	6,690
4x4	6.2L	14,000	7,550	14,000	6,930	14,000	7,200	14,000	7,040
	6.7L	14,000	6,800	14,000	6,740	14,000	5,880	14,000	6,280

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts
8/6/2018

F-450 DRW Chassis Cab
Standard Fixed 16,500 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)	GVWR (lbs.)	Payload (lbs.)
Drive	Engine																
4x2	6.8L	16,500	9,850	16,500	9,790	16,500	9,610	16,500	9,550	16,500	9,550	16,500	9,360	16,500	9,380	16,500	9,230
	6.7L	16,500	9,110	16,500	9,040	16,500	8,860	16,500	8,800	16,500	8,800	16,500	8,590	16,500	8,650	16,500	8,480
4x4	6.8L	16,500	9,540	16,500	9,450	16,500	9,300	16,500	9,230	16,500	9,190	16,500	9,030	16,500	9,070	16,500	8,940
	6.7L	16,500	8,790	16,500	8,710	16,500	8,550	16,500	8,480	16,500	8,440	16,500	8,270	16,500	8,330	16,500	8,190

F-450 DRW Chassis Cab
Optional Fixed 15,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
Drive	Engine																
4x2	6.8L	15,000	8,350	15,000	8,290	15,000	8,110	15,000	8,050	15,000	8,050	15,000	7,860	15,000	7,880	15,000	7,730
	6.7L	15,000	7,610	15,000	7,540	15,000	7,360	15,000	7,300	15,000	7,300	15,000	7,090	15,000	7,150	15,000	6,980
4x4	6.8L	15,000	8,040	15,000	7,950	15,000	7,800	15,000	7,730	15,000	7,690	15,000	7,530	15,000	7,570	15,000	7,440
	6.7L	15,000	7,290	15,000	7,210	15,000	7,050	15,000	6,980	15,000	6,940	15,000	6,770	15,000	6,830	15,000	6,690

F-450 DRW Chassis Cab
Optional Fixed 16,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
Drive	Engine																
4x2	6.8L	16,000	9,350	16,000	9,290	16,000	9,110	16,000	9,050	16,000	9,050	16,000	8,860	16,000	8,880	16,000	8,730
	6.7L	16,000	8,610	16,000	8,540	16,000	8,360	16,000	8,300	16,000	8,300	16,000	8,090	16,000	8,150	16,000	7,980
4x4	6.8L	16,000	9,040	16,000	8,950	16,000	8,800	16,000	8,730	16,000	8,690	16,000	8,530	16,000	8,570	16,000	8,440
	6.7L	16,000	8,290	16,000	8,210	16,000	8,050	16,000	7,980	16,000	7,940	16,000	7,770	16,000	7,830	16,000	7,690

2019 SUPER DUTY F-SERIES TRUCKS
Maximum Payload Package Selector Charts
8/6/2018

F-550 DRW Chassis Cab
Standard 18,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.8L	18,000	11,350	18,000	11,290	18,000	11,110	18,000	11,050	18,000	11,050	18,000	10,860	18,000	10,880	18,000	10,730
	6.7L	18,000	10,610	18,000	10,540	18,000	10,360	18,000	10,300	18,000	10,300	18,000	10,090	18,000	10,150	18,000	9,980
4x4	6.8L	18,000	11,040	18,000	10,950	18,000	10,800	18,000	10,730	18,000	10,690	18,000	10,530	18,000	10,570	18,000	10,440
	6.7L	18,000	10,290	18,000	10,210	18,000	10,050	18,000	9,980	18,000	9,940	18,000	9,770	18,000	9,830	18,000	9,690

F-550 DRW Chassis Cab
Optional 17,500 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.8L	17,500	10,850	17,500	10,790	17,500	10,610	17,500	10,550	17,500	10,550	17,500	10,360	17,500	10,380	17,500	10,230
	6.7L	17,500	10,110	17,500	10,040	17,500	9,860	17,500	9,800	17,500	9,800	17,500	9,590	17,500	9,650	17,500	9,480
4x4	6.8L	17,500	10,540	17,500	10,450	17,500	10,300	17,500	10,230	17,500	10,190	17,500	10,030	17,500	10,070	17,500	9,940
	6.7L	17,500	9,790	17,500	9,710	17,500	9,550	17,500	9,480	17,500	9,440	17,500	9,270	17,500	9,330	17,500	9,190

F-550 DRW Chassis Cab
Optional 19,000 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.8L	19,000	12,310	---	---	---	---	---	---	---	---	---	---	---	---	---	---
4x4	6.8L	19,000	12,000	---	---	---	---	---	---	---	---	---	---	---	---	---	---

F-550 DRW Chassis Cab
Optional 19,500 GVWR

		Regular Cab								SuperCab				Crew Cab			
		60" CA		84" CA		108" CA		120" CA		60" CA		84" CA		60" CA		84" CA	
		GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)	GVWR (lbs.)	Max Payload (lbs.)
4x2	6.8L	---	---	19,500	12,750	19,500	12,570	19,500	12,510	19,500	12,510	19,500	12,320	19,500	12,340	19,500	12,190
	6.7L	19,500	12,070	19,500	12,000	19,500	11,820	19,500	11,760	19,500	11,760	19,500	11,550	19,500	11,610	19,500	11,440
4x4	6.8L	---	---	19,500	12,410	19,500	12,260	19,500	12,190	19,500	12,150	19,500	11,990	19,500	12,030	19,500	11,900
	6.7L	19,500	11,750	19,500	11,670	19,500	11,510	19,500	11,440	19,500	11,400	19,500	11,230	19,500	11,290	19,500	11,150

2019 SUPER DUTY F-SERIES TRUCKS
Snow Plow Application Charts

8/6/2018

F-250-450 4x4 Pickup/Box Delete Models (with Driver and One Passenger)

Cab	Wheelbase (in.)	Engine	F-250 4x4 (17" tire)*	F-350 SRW 4x4 (18" tire)*	F-350 DRW 4x4	F-350 DRW 4x4 (box delete)	F-450 4x4
Regular Cab	141.6	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8	100/1005	100/1005	100/1005	100/1005	100/800
SuperCab	148	6.2L V8	100/1005	100/1005	X	X	X
		6.7L V8	100/950	100/900	X	X	X
	164.2	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8	100/800	100/800	100/800	100/800	X
Crew Cab	159.8	6.2L V8	100/1005	100/1005	X	X	X
		6.7L V8	100/850	100/850	X	X	X
	176	6.2L V8	100/1005	100/1005	100/1005	X	X
		6.7L V8	100/700	100/700	100/650	100/650	100/550

* Considering max. GAWR and A/T tires. 100/750= Maximum 100 lbs. of permanently attached hardware/maximum 750 lbs. of removable plow blade and hardware. The plow and hardware weight limits are shown based upon a vehicle with 33% Ford option content and 300 lbs for the driver and front-seat passenger (150 lbs each). This chart ONLY shows maximum recommended values.

Legend:

X = Not recommended for snow plow application. Snow Plow Package not available.

F-350 4x4 and F-450/F-550 4x2/4x4 Chassis Cab Models (with Driver and One Passenger)

Cab	Wheelbase/ CA (in.)	Engine	F-350 SRW 4X4	F-350 4x4 14,000-lb. GVWR	F-450 4x2 16,500-lb. GVWR	F-450 4x4 16,500-lb. GVWR	F-550 4x2 18,000-lb. GVWR	F-550 4x4 18,000-lb. GVWR	F-550+ 4x2 19,000/19,500-lb. GVWR	F-550+ 4x4 19,000/19,500-lb. GVWR
Regular Cab	145.3/60	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/950	100/950	100/1350	100/1250	100/1350	100/1200	100/1350	100/1250
	169.3/84	6.2L V8	X	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	100/900	100/1350	100/1250	100/1350	100/1200	100/1350	100/1200
	193.3/108	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1200	100/1350	100/1150	100/1350	100/1150
	205.3/120	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1150	100/1350	100/1100	100/1350	100/1150
SuperCab	167.9/60	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/850	100/800	100/1350	100/1250	100/1350	100/1200	100/1350	100/1200
	191.9/84	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1150	100/1350	100/1100	100/1350	100/1100
Crew Cab	179.8/60	6.2L V8	100/1005	100/1005	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	100/800	100/750	100/1350	100/1150	100/1350	100/1150	100/1350	100/1100
	203.8/84	6.2L V8	X	X	X	X	X	X	X	X
		6.8L V10	X	X	100/1350	100/1350	100/1350	100/1350	100/1350	100/1350
		6.7L V8	X	X	100/1350	100/1100	100/1300	100/1050	100/1300	100/1050

100/750= Maximum 100 lbs. of permanently attached hardware. Maximum 750 lbs. of removable plow blade and hardware (maximum plow system weight is the sum of these). The plow and hardware weight limits are shown based upon a vehicle with maximum buildable option content and 300 lbs for the driver and front-seat passenger (150 lbs each). This chart ONLY shows maximum recommended values.

Legend:

X = Unavailable vehicle configuration.

2019 SUPER DUTY F-SERIES TRUCKS
Cab-to-Axle Dimension Chart

8/6/2018

Model	Cab	Wheelbase (in.)	Cab-to-Axle (CA) (in.)	Pickup	Box Delete	Chassis Cab
F-250	Regular Cab	141.6	56.1	8' Box	Yes	--
	SuperCab	148.0	39.9	6.75' Box	--	--
		164.2	56.1	8' Box	Yes	--
	Crew Cab	159.8	39.9	6.75' Box	--	--
		176.0	56.1	8' Box	Yes	--
F-350	Regular Cab	141.6	56.1	8' Box	Yes	--
		145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
	SuperCab	148.0	39.9	6.75' Box	--	--
		164.2	56.1	8' Box	Yes	--
		167.9	60.0	--	--	Yes
	Crew Cab	159.8	39.9	6.75' Box	--	--
		176.0	56.1	8' Box	Yes	--
		179.8	60.0	--	--	Yes
F-450	Regular Cab	141.6	56.1	8' Box	--	--
		145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
		193.3	108.0	--	--	Yes
		205.3	120.0	--	--	Yes
	SuperCab	167.9	60.0	--	--	Yes
		191.9	84.0	--	--	Yes
	Crew Cab	176.0	56.1	8' Box	--	--
		179.8	60.0	--	--	Yes
F-550	Regular Cab	203.8	84.0	--	--	Yes
		145.3	60.0	--	--	Yes
		169.3	84.0	--	--	Yes
		193.3	108.0	--	--	Yes
	SuperCab	205.3	120.0	--	--	Yes
		167.9	60.0	--	--	Yes
	Crew Cab	191.9	84.0	--	--	Yes
		179.8	60.0	--	--	Yes
	Crew Cab	203.8	84.0	--	--	Yes
		179.8	60.0	--	--	Yes

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Chart

8/6/2018

F-250 Pickup/Pickup Box Delete

Heavy Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection
	4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Snow Plow Package	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,800	3,950	1 UP	2 UP	---
	6.7L	4,400	4,550	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	4,800	4,800	1 UP	1 UP	5,990
SuperCab 4x2/148.0	6.2L	3,800	4,100	1 UP	2 UP	---
	6.7L	4,550	4,850	1 UP	2 UP	---
SuperCab 4x2/164.2	6.2L	4,100	4,400	1 UP	2 UP	---
	6.7L	4,850	5,000	1 UP	2 UP	---
SuperCab 4x4/148.0	6.2L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	4,800	5,200	1 UP	1 UP	5,990
SuperCab 4x4/164.2	6.2L	4,800	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,600	1 UP	1 UP	5,990
Crew Cab 4x2/159.8	6.2L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,700	4,850	1 UP	2 UP	---
Crew Cab 4x2/176.0	6.2L	4,250	4,400	1 UP	2 UP	---
	6.7L	4,850	5,250	1 UP	2 UP	---
Crew Cab 4x4/159.8	6.2L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	5,990
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	5,990
	6.7L	5,200	5,600	1 UP	1 UP	5,990

Please refer to the [Body Builder's Layout Book](#) for further information regarding front GAWR.

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Chart

8/6/2018

F-350 SRW Pickup/Pickup Box Delete
Standard/Variable GVWR for 17" Wheel & Tire

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,800	3,950	1 UP	2 UP	---
	6.7L	4,400	4,550	1 UP	2 UP	
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	4,800	5,200	1 UP	1 UP	5,990
SuperCab 4x2/148.0	6.2L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,550	4,700	1 UP	2 UP	
SuperCab 4x2/164.2	6.2L	4,250	4,400	1 UP	2 UP	---
	6.7L	4,850	5,000	1 UP	2 UP	
SuperCab 4x4/148.0	6.2L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	4,800	5,200	1 UP	1 UP	5,990
SuperCab 4x4/164.2	6.2L	4,800	4,800	1 UP	1 UP	5,990
	6.7L	5,200	5,600	1 UP	1 UP	5,990
Crew Cab 4x2/159.8	6.2L	3,950	4,400	1 UP	2 UP	---
	6.7L	4,550	4,850	1 UP	2 UP	
Crew Cab 4x2/176.0	6.2L	4,400	4,700	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	
Crew Cab 4x4/159.8	6.2L	4,400	4,800	1 UP	1 UP	5,990
	6.7L	5,200	5,600	1 UP	1 UP	5,990
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	5,990
	6.7L	5,600	5,600	1 UP	1 UP	5,990

Please refer to the [Body Builder's Layout Book](#) for further information regarding front GAWR.

F-350 SRW Pickup/Pickup Box Delete
Standard/Optional GVWR for 18" Wheel & Tire

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	3,800	3,950	1 UP	2 UP	---
	6.7L	4,550	4,550	1 UP	2 UP	
Regular Cab 4x4/141.6	6.2L	4,400	4,400	1 UP	1 UP	5,600
	6.7L	4,800	5,200	1 UP	1 UP	5,990
SuperCab 4x2/148.0	6.2L	3,950	4,250	1 UP	2 UP	---
	6.7L	4,550	4,850	1 UP	2 UP	
SuperCab 4x2/164.2	6.2L	4,250	4,550	1 UP	2 UP	---
	6.7L	4,850	5,000	1 UP	2 UP	
SuperCab 4x4/148.0	6.2L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	5,990
SuperCab 4x4/164.2	6.2L	4,800	4,800	1 UP	1 UP	5,990
	6.7L	5,200	5,600	1 UP	1 UP	5,990
Crew Cab 4x2/159.8	6.2L	4,100	4,250	1 UP	2 UP	---
	6.7L	4,700	4,850	1 UP	2 UP	
Crew Cab 4x2/176.0	6.2L	4,400	4,700	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	
Crew Cab 4x4/159.8	6.2L	4,400	4,800	1 UP	1 UP	5,990
	6.7L	5,200	5,600	1 UP	1 UP	5,990
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	5,990
	6.7L	5,600	5,600	1 UP	1 UP	5,990

Please refer to the [Body Builder's Layout Book](#) for further information regarding front GAWR.

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Chart

8/6/2018

The standard front spring/GAWR⁽¹⁾ on pickup models is computer-selected based on the total front weight of options ordered. Front spring/GAWR upgrades are in increments of 150 lbs. on 4x2 models with spring ratings from 3,800 lbs. to 5,250 lbs. and in increments of 400 lbs. on 4x4 models with spring ratings from 4,400 lbs. to 6,000 lbs. Certain option packages include the following front spring/GAWR upgrades:

F-350 DRW Pickup/Pickup Box Delete⁽²⁾

Heavy Service Suspension Package	Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Camper Package	4x2: Front springs/GAWR will be selected 2 upgrades higher than standard computer selection
	4x4: Front springs/GAWR will be selected 1 upgrade higher than standard computer selection
Snow Plow Package	Front springs/GAWR is assigned or specifically selected as shown in the chart below.

Front spring/GAWR upgrade is not included if the maximum front spring has been computer-selected as a consequence of options ordered.

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Camper Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.2L	4,100	4,100	1 UP	2 UP	---
	6.7L	4,550	4,700	1 UP	2 UP	---
Regular Cab 4x4/141.6	6.2L	4,400	4,800	1 UP	1 UP	5,600
	6.7L	5,200	5,200	1 UP	1 UP	5,990
SuperCab 4x2/164.2	6.2L	4,400	4,550	1 UP	2 UP	---
	6.7L	5,000	5,250	1 UP	2 UP	---
SuperCab 4x4/164.2	6.2L	4,800	5,200	1 UP	1 UP	5,990
	6.7L	5,600	5,600	1 UP	1 UP	5,990
Crew Cab 4x2/176.0	6.2L	4,550	4,700	1 UP	2 UP	---
	6.7L	5,250	5,250	1 UP	2 UP	---
Crew Cab 4x4/176.0	6.2L	4,800	5,200	1 UP	1 UP	5,990
	6.7L	5,600	5,990	1 UP	1 UP	5,990

F-350 DRW Pickup Box Delete (13,000 lbs. GVWR)⁽²⁾

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy Duty Front Suspension Package (lbs.) 5,250-lb. Maximum (4x2) 5,990-lb. Maximum (4x4)	Snow Plow Package (lbs.)
		Minimum	Maximum		
Regular Cab 4x2/141.5	6.7L	4,550	4,700	1 UP	-
Regular Cab 4x4/141.5	6.7L	5,200	5,200	1 UP	5,990
Super Cab 4x2/164.1	6.7L	5,000	5,250	1 UP	-
Super Cab 4x4/164.1	6.7L	5,600	5,600	1 UP	5,990
Chassis Cab 4x2/175.9	6.7L	5,250	5,250	1 UP	-
Chassis Cab 4x4/175.9	6.7L	5,600	5,990	1 UP	5,990

(1) Gross Axle Weight Rating is determined by the rated capacity of the minimum component of the axle system (axle, computer-selected springs, wheels, tires) of a specific vehicle. Front and rear GAWRs will, in all cases, sum to a number equal to or greater than the GVWR for the particular vehicle. Maximum loaded vehicle (including passengers, equipment and payload) cannot exceed the GVW rating or GAWR (front or rear).

(2) The spring selection process also applies to F-250 and F-350 SRW.

Please refer to the [Body Builder's Layout Book](#) for further information regarding front GAWR.

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts

8/6/2018

F-450 Pickup - Standard GVWR

Cab Style Drive/WB (in.)	Engine	Front GAWR (lbs.) Standard		Heavy Duty Front Suspension Package (lbs.) 1 UP	Camper Package (lbs.) 1 UP	Snow Plow Package (lbs.)
		Minimum	Maximum			
Regular Cab 4x2/141.6	6.7L	5,200	5,200	6,000	6,000	—
Regular Cab 4x4/141.6	6.7L	5,200	5,600	6,000	6,000	6,000
Crew Cab 4x2/176.0	6.7L	5,600	5,600	6,000	6,000	—
Crew Cab 4x4/176.0	6.7L	5,600	6,000	6,000	6,000	6,000

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts

8/6/2018

F-350 SRW Chassis Cabs - Standard GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard/ Optional (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package ⁽¹⁾ (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	9,800	4,250	4,400	4,550	---	---	---
	6.7L	9,800	4,700	4,850	5,000	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	9,800	4,400	4,800	5,200	---	---	5,600
	6.7L	9,800	5,200	5,600	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	9,800	4,400	4,550	4,700	---	---	---
	6.7L	9,800	5,000	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	9,800	4,800	5,200	5,600	----	----	5,990
	6.7L	9,800	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	9,800	4,550	4,700	4,850	----	----	---
	6.7L	9,800	5,250	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	9,800	5,200	5,600	5,990	----	----	5,990
	6.7L	9,800	5,600	5,990	5,990	5,990	5,990	5,990

F-350 SRW Chassis Cabs - 10,000-lb. GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard/ Optional (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package ⁽¹⁾ (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	10,000	4,100	4,250	4,400	---	---	---
	6.7L	10,000	4,700	4,850	5,000	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	10,000	4,400	4,800	5,200	---	---	5,600
	6.7L	10,000	5,200	5,600	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	10,000	4,400	4,550	4,700	---	---	---
	6.7L	10,000	5,250	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	10,000	4,800	5,200	5,600	----	----	5,990
	6.7L	10,000	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	10,000	4,550	4,700	4,850	----	----	---
	6.7L	10,000	5,250	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	10,000	5,200	5,600	5,990	----	----	5,990
	6.7L	10,000	5,600	5,990	5,990	5,990	5,990	5,990

F-350 SRW Chassis Cabs - Variable GVWR

Cab Style Drive/WB (in.)	Engine	GVWR (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package ⁽¹⁾ (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	10,500	4,100	4,250	4,400	---	---	---
	6.7L	11,100	4,550	4,700	4,850	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	10,900	4,400	4,800	5,200	----	----	5,600
	6.7L	11,500	5,200	5,600	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	10,900	4,400	4,550	4,700	----	----	---
	6.7L	11,500	5,000	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	11,300	4,800	5,200	5,600	----	----	5,990
	6.7L	11,500	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	11,000	4,550	4,700	4,850	----	----	---
	6.7L	11,500	5,000	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	11,400	4,800	5,200	5,600	----	----	5,990
	6.7L	11,500	5,600	5,990	5,990	5,990	5,990	5,990

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts

8/6/2018

F-350 DRW Chassis Cabs

Cab Style Drive/WB (in.)	Engine	GVWR (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package⁽¹⁾ (lbs.)	Snow Plow Package (lbs.)
Regular Cab 4x2/145.3	6.2L	14,000	4,250	4,400	4,550	----	----	---
	6.7L	14,000	4,850	5,000	5,250	5,250	5,250	---
Regular Cab 4x2/169.3	6.2L	14,000	4,700	4,850	5,000	----	----	---
	6.7L	14,000	5,250	5,250	5,250	5,250	5,250	---
Regular Cab 4x4/145.3	6.2L	14,000	4,800	5,200	5,600	----	----	5,990
	6.7L	14,000	5,200	5,600	5,990	5,990	5,990	5,990
Regular Cab 4x4/169.3	6.2L	14,000	5,200	5,600	5,990	----	----	5,990
	6.7L	14,000	5,600	5,990	5,990	5,990	5,990	5,990
SuperCab 4x2/167.9	6.2L	14,000	4,550	4,700	4,850	----	----	---
	6.7L	14,000	5,250	5,250	5,250	5,250	5,250	---
SuperCab 4x4/167.9	6.2L	14,000	5,200	5,600	5,990	----	----	5,990
	6.7L	14,000	5,600	5,990	5,990	5,990	5,990	5,990
Crew Cab 4x2/179.8	6.2L	14,000	4,700	4,850	5,000	----	----	---
	6.7L	14,000	5,250	5,250	5,250	5,250	5,250	---
Crew Cab 4x4/179.8	6.2L	14,000	5,200	5,600	5,990	----	----	5,990
	6.7L	14,000	5,600	5,990	5,990	5,990	5,990	5,990

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts
8/6/2018

F-450 Chassis Cabs - Standard 16,500 lb. & Optional 16,000/15,000 lb. GVWR										
Cab Style Drive/WB (in.)	Engine	GVWR Standard/Opt./Opt. (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package ⁽¹⁾ (lbs.)	Wrecker Package (lbs.)	Snow Plow Package (lbs.)	Extra Heavy Duty Front End Suspension ⁽²⁾ (lbs.)
Regular Cab 4x2/145.3	6.8L	16,500/16,000/15,000	4,800	5,200	5,600	7,000	----	7,000	6,500	7,500
	6.7L	16,500/16,000/15,000	5,200	5,600/5,600/6,000	6,000/6,000/6,500	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/169.3	6.8L	16,500/16,000/15,000	5,200	5,600	6,000	7,000	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,000/5,600/5,600	6,500/6,000/6,000	7,000/6,500/6,500	7,000	7,000	----	7,000	7,500
Regular Cab 4x2/193.3	6.8L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,500/6,500/6,000	7000/7000/6500	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x2/205.3	6.8L	16,500/16,000/15,000	6,000/5,600/5,600	6,500/6,000/6,000	7,000/6,500/6,500	7,000	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x4/145.3	6.8L	16,500/16,000/15,000	4,800	5,200	5,600	7,000	----	7,000	6,500	7,500
	6.7L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/169.3	6.8L	16,500/16,000/15,000	5,600/5,600/5,200	6,000/6,000/5,600	6,500/6,500/6,000	7,000	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x4/193.3	6.8L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
Regular Cab 4x4/205.3	6.8L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
SuperCab 4x2/167.9	6.8L	16,500/16,000/15,000	5,200/5,200/4,800	5600/5600/5200	6000/6000/5600	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	7,000	----	7,000	7,500
SuperCab 4x2/191.9	6.8L	16,500/16,000/15,000	5,600	6,000	6,500	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
SuperCab 4x4/167.9	6.8L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
SuperCab 4x4/191.9	6.8L	16,500/16,000/15,000	6000/6000/5600	6,500/6,500/6,000	7,000/7,000/6,500	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500
Crew Cab 4x2/179.8	6.8L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	5,600	6,000	6,500	7,000	7,000	----	7,000	7,500
Crew Cab 4x2/203.8	6.8L	16,500/16,000/15,000	5,600	6,000	6,500	----	----	----	6,500	7,500
	6.7L	16,500/16,000/15,000	6,500/6,000/6,000	7,000/6,500/6,500	7,000	7,000	7,000	----	7,000	7,500
Crew Cab 4x4/179.8	6.8L	16,500/16,000/15,000	5,200	5,600	6,000	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,000	6,500	7,000	7,000	7,000	----	7,000	7,500
Crew Cab 4x4/203.8	6.8L	16,500/16,000/15,000	6,000/6,000/5,600	6,500/6,500/6,000	7,000/7,000/6,500	----	----	----	7,000	7,500
	6.7L	16,500/16,000/15,000	6,500	7,000	7,000	7,000	7,000	----	7,000	7,500

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register voids the Ford Warranty.
(2) Requires 4.30 or 4.88 axle ratio.

2019 SUPER DUTY F-SERIES TRUCKS
Front GAWR Selection Charts

8/6/2018

F-550 Chassis Cabs - Standard/Optional GVWR

Cab Style Drive/WB (in.)	Engine	GVWR Standard/Opt./Opt. (lbs.)	Front GAWR Max. Standard (lbs.)	Heavy-Service Suspension Package (lbs.)	Extra Heavy-Service Suspension Package (lbs.)	Ambulance Prep Package (lbs.)	Fire/Rescue Prep Package ⁽¹⁾ (lbs.)	Snow Plow Package (lbs.)	Extra Heavy Duty Front End Suspension ⁽²⁾ (lbs.)
Regular Cab 4x2/145.3	6.8L	18,000/17,500/19,000	4,800/4,800/5,600	5,200/5,200/6,000	5,600/5,600/6,500	7,000	----	6,500	7,500
	6.7L	18,000/17,500/19,500	5,200	5,600	6,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/169.3	6.8L	18,000/17,500/19,500	5,600/5,200/5,600	6,000/5,600/6,000	6,500/6,000/6,500	7,000	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/193.3	6.8L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500/6,500/7,000	7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x2/205.3	6.8L	18,000/17,500/19,500	6,000/6,000/6,500	6,500/6,500/7,000	7,000	7,000	----	6,500/6,500/7,000	7,500
	6.7L	18,000/17,500/19,500	6,500/6,500/7,000	7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/145.3	6.8L	18,000/17,500/19,000	5,200/5,200/5,600	5,600/5,600/6,000	6,000/6,000/6,500	7,000	----	7,000	7,500
	6.7L	18,000/17,500/19,500	5,600	6,000	6,500	7,000	7,000	7,000	7,500
Regular Cab 4x4/169.3	6.8L	18,000/17,500/19,500	5,600	6,000	6,500	7,000	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,500/6,000/6,500	7,000/6,500/7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/193.3	6.8L	18,000/17,500/19,500	6,500/6,000/6,500	7,000/6,500/7,000	7,000	7,000	----	7,000	7,500
	6.7L	18,000/17,500/19,500	7,000	7,000	7,000	7,000	7,000	7,000	7,500
Regular Cab 4x4/205.3	6.8L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	----	7,000	7,500
	6.7L	18,000/17,500/19,500	7,000	7,000	7,000	7,000	7,000	7,000	7,500
SuperCab 4x2/167.9	6.8L	18,000/17,500/19,500	5,200	5,600	6,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	5,600	6,000	6,500	7,000	7,000	7,000	7,500
SuperCab 4x2/191.9	6.8L	18,000/17,500/19,500	5,600	6,000/6,000/6,500	6,500/6,500/7,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500
SuperCab 4x4/167.9	6.8L	18,000/17,500/19,500	5,200/5,200/5,600	5,600/5,600/6,000	6,000/6,000/6,500	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	7,000	7,000	7,500
SuperCab 4x4/191.9	6.8L	18,000/17,500/19,500	6,000	6,500	7,000	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500
Crew Cab 4x2/179.8	6.8L	18,000/17,500/19,500	5,200	5,600	6,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	5,600/5,600/6,000	6,000/6,000/6,500	6,500/6,500/7,000	7,000	7,000	7,000	7,500
Crew Cab 4x2/203.8	6.8L	18,000/17,500/19,500	5,600/5,600/6,000	6,000/6,000/6,500	6,500/6,500/7,000	----	----	6,500	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500
Crew Cab 4x4/179.8	6.8L	18,000/17,500/19,500	5,600	6,000	6,500	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,000	6,500	7,000	7,000	7,000	7,000	7,500
Crew Cab 4x4/203.8	6.8L	18,000/17,500/19,500	6,000	6,500	7,000	----	----	7,000	7,500
	6.7L	18,000/17,500/19,500	6,500	7,000	7,000	7,000	7,000	7,000	7,500

(1) Ford vehicles equipped with the Fire/Rescue Prep Package with Special Emissions – for Diesel Engine (47J) NOT completed as Emergency Vehicles as defined per 40 CFR 86.1803.01 in the Federal Register **voids** the Ford Warranty.

(2) Requires 4.30 or 4.88 axle ratio.